



Notes:

Quality Seal Multi-Pocket Polyester Cube Filters offer up to five times the filter area of flat panels. One, Two, and Three pocket configurations in any media or combination of medias are available. Quality Seal Multi-Pocket Polyester Cube Filters are the best way to maximize the service life and efficiency of the "Quality Seal" polyester medias. Double wire frame construction encapsulates the media, providing a self sealing support that also withstands warping from heavy loading and aggressive installation. Polyester overlap around the edges inhibits dust and paint bypass. Ideal for HVAC or Paint Overspray collection. Aerospace systems are available.

Media Area (sq. ft.) 1" Tackified

Face Dimensions	1 Pkt Square Cubes			2 Pkt Tapered Cubes		
	Depth	12"	15"	20"	12"	15"
12x24	8.00	9.50	12.00	-	-	-
16x20	8.22	9.72	12.22	8.67	10.83	14.44
16x25	9.61	11.32	14.17	10.33	12.92	17.22
20x20	9.44	11.11	13.89	9.17	11.46	15.28
20x24	10.67	12.50	15.56	10.50	13.13	17.50
20x25	10.97	12.85	15.97	10.83	13.54	18.06
24x24	12.00	14.00	17.33	11.00	13.75	18.33
Face Dimensions	2 Pkt Triangular Cubes				3 Pkt Tapered Cubes	
	Depth	13"	14"	16"	18"	12"
12x24	6.71	-	-	-	-	-
20x20		7.86	-	-	13.75	17.19
20x25			10.0	-	16.25	20.31
24x24				11.31	16.50	20.63

Typical Performance Data (24x24x15 - 3 Pocket Filter)

Product Code	ASHRAE 52.2 - 1999				Initial Resistance "w.g. @ 300 fpm	Final Resistance "w.g.
	MERV Value	E1 %	E2 %	E3 %		
CF31T	< 5	n/a	n/a	n/a	0.02	1.00

Part Number Guide

Product Code	Pocket Count*	Media	Dimensions	Header	No Support Wire
CF	1	1" Tackified	WxHxD	H	X

Examples:

CF11T122412 = Cube Filter, 1 Pkt, 1" Tackified Media, 12x24x12

CF31T202015H = Cube Filter, 3 Pkt, 1" Tackified Media, 20x20x15, with Header

*Q denotes 2 triangle shaped pockets

Characteristics	Quality Seal Multi-Pocket Cube Filters
Filter Media	1 inch thick; 15 and 40 denier polyester blend with a non-migrating dry tackified downstream surface.
Construction Technique	Sewn pockets with hog ring fasteners
Support Frames	Two 0.148 inch (9 gage) galvanized steel wire frames
Max. Temperature	100°F (38°C) continuous service, Peaks to 120°F, (49°C)
Max. Humidity	Resistant to 100% R.H.



QUALITY FILTERS, INC.
 THINK SIMPLE. THINK SMART. THINK QUALITY.

23351 Grissom Drive
 Robertsdale, AL 36567
 www.QualityFilters.com

Phone: (251) 947-2400
 Order Fax: (251) 947-2499
 Sales Fax: (251) 947-7948

**QUALITY SEAL - 1" Tackified Media
 Multi-Pocket Polyester Cube Filters**

DR JJS	Date 29 Sep 07	Dwg No.	Q-110006	Revision A
CK JH	Date 29 Sep 07			